


Tungsten Fresnel 24kW/20kW Studio

LAMPHEAD CONTENTS

- Lamp Housing without Bulb # (purple grey & silver color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Ø625mm (24-5/8 in.) Fresnel Lens
- Inlet Cable 2.5m (8.2 ft.) *
- Stirrup with Ø28mm (1-1/8 in.) Spigot
 - * No switch (Rotary or Panel switch on request) # Requires Lamp Bulb

DIMENSIONS (mm)



Tungsten Fresnel 24kW/20kW Studio

SPECIFICATIONS

Identity No.	L24020TF	
Capacity	24,000W / 20,000W	
Voltage	200 - 240V AC	
Fresnel Lens	Ø625mm (24-5/8 in.)	
Lamp Type	24kW/20kW SE	
Color Temp.	3200K	
Lamp Holder	G38	
Stirrup	Ø28mm (1-1/8 in.) Spigot	
Class / IP Rating	1 / IP 23	
Max. Surface Temp.	240 °C	
Max. Ambient Temp.	45 °C	
Min. Distance to Illuminated Object	12m	
Min. Distance to Flammable Object	2.5m	
Operating Range	+30° ~ 0° ~ -30°	
Weight (lamphead)	63kg	
Weight (with barndoor)	69.5kg	
·	·	

ACCESSORIES

4-leaf Rotatable Barndoor

Set of 4 Scrims Ø736mm (29 in.):

Full Single, Full Double, Half Single, Half Double

Scrim Bag

Safety Cable (for lamphead)

Safety Wire (for barndoor)

24kW Electronic Dimmer with cable (only for TF 24kW/20kW)

PHOTOMETRIC DATA

	10m	15m	20m
24000W Studio			
Spot (13°) Lux Beam Ø	46763 2.28 m	20784 3.42 m	11691 4.56 m
Flood (56°) Lux Beam Ø	8019 10.63 m	3564 15.95 m	2005 21.27 m

FILM GEAR INT. reserves the right to change or alter any of the items detailed on this page, to increase or improve manufacturing techniques without prior notice. @ 20230822