



## Daylight Broad 6000W

### LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey & silver color)
- 537 x 479 x 2.75 (mm) Protective Lens
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm (1-1/8 in.) Spigot

# Requires Electronic Ballast,  
Lamphead to Ballast Cable and Lamp Bulb

## Daylight Broad 6000W

### SPECIFICATIONS

Identity No.	L06000DB
Capacity	6,000W
Lamp Bulb Voltage	125V
Protective Lens Size	537 x 479 x 2.75 (mm)
Lamp Type	DIS-60H 6000W SE
Color Temp.	5600K
Lamp Holder	GX38
Stirrup	Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 20
Max. Surface Temp.	190°C
Max. Ambient Temp.	45°C
Min. Distance to Illuminated Object	12 m
Min. Distance to Flammable Object	1.5 m
Operating Range	+45° - 0° - -45°
Weight (Lamphead)	33.5 kg

### ACCESSORIES

Electronic Ballast V3 : 12kW/6kW or 9kW/6kW or 6000W

Lamphead to Ballast Cable : 7m (23 ft.) or 15m (49 ft.)

4-leaf Barndoor

Black Skirt

Silk Skirt

Target Assembly

Filter Frame

Safety Cable (for lamphead)

Safety Wire (for barndoor)

### DIMENSIONS (mm)

