



Daylight Fresnel 18kW/12kW DE

LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey & silver color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Ø625mm (24-5/8 in.) Fresnel Lens
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm (1-1/8 in.) Spigot

Requires Electronic Ballast, Lamphead to Ballast Cable and Lamp Bulb

Daylight Fresnel 18kW/12kW DE



SPECIFICATIONS

| | |
|-------------------------------------|--------------------------------|
| Identity No. | L18012DD |
| Capacity | 18,000W / 12,000W |
| Lamp Bulb Voltage | 225V / 160V |
| Fresnel Lens | Ø625mm (24-5/8 in.) |
| Lamp Type | HMI 18000W/DE or HMI 12000W/DE |
| Color Temp. | 5600K |
| Lamp Holder | Double-End Spring loaded |
| Stirrup | Ø28mm (1-1/8 in.) Spigot |
| Class / IP Rating | 1 / IP 20 |
| Max. Surface Temp. | 230 °C |
| Min. Distance to Illuminated Object | 15m |
| Min. Distance to Flammable Object | 2m |
| Operating Range | +30° ~ 0° ~ -30° |
| Weight (lamphead) | 92kg |
| Weight (with barndoor) | 98.8kg |

ACCESSORIES

- Electronic Ballast V3 : 18kW/12kW
- Lamphead to Ballast Cable : 15m (49 ft.) or 20m (66 ft.)
- 4-leaf Rotatable Barndoor
- Set of 4 Scrims Ø737mm (29 in.) : Full Single, Full Double, Half Single, Half Double
- Scrim Bag
- Safety Cable (for lamphead)
- Safety Wire (for barndoor)

PHOTOMETRIC DATA



DIMENSIONS (mm)

